



ANGLE BROOM

REQUIREMENTS	FEATURES & BENEFITS
<div style="display: flex; justify-content: space-around; margin-top: 10px;"> <div style="text-align: center;"> <p>Angle Broom</p> </div> <div style="text-align: center;"> <p>Attachment Control Kit</p> </div> </div> <p style="font-size: small; margin-top: 10px;">Angle Broom: Loader must be equipped with an Attachment Control Kit.</p>	<ul style="list-style-type: none"> Sweep flush to a curb or wall on right side. Adjust the broom angle with fingertip controls on a cab-mounted attachment control kit (sold separately). 122 cm Angle Broom has 3-position manual angle. High-torque motor for heavy material. Proven, replaceable wafer bristles. Polypropylene bristle material for long life.

Description: Dirt, dried mud, light snow and other debris are quickly and efficiently swept away with this hydraulically driven attachment. Whether you're sweeping driveways, farmyards or warehouses, you can depend on the angle broom to get the job done right.

TECHNICAL SPECIFICATIONS										
Description	Part Number	Sweeping Width (mm)	Sweeping Width Fully Angled (mm)	Brush Diameter (mm)	Number of Bristle Sections (zigzag - straight)	Degree of Angle	Flow Range (L/min)	Control Kit Required	Working Flow	First Use Installation Time
Angle Broom, 122 cm	6907000	1219	1055 @ 30°	543	23 - 4	± 30° (manual)	30 - 50	No	Standard	None
Angle Broom, 173 cm, ACD	6905805	1727	1600 @ 25°	813	33 - 2	± 25° (hydr. cyl.)	30 - 68	Yes	Standard / High Flow	None
Angle Broom, 213 cm, ACD	6905806	2134	1956 @ 25°	813	48 - 2	± 25° (hydr. cyl.)	57 - 106	Yes	Standard / High Flow	None

COMPATIBILITY CHARTS		Compact Track Loaders								Skid Steer Loaders and All-Wheel Steer Loaders													
Description	Part Number																						
		MT55	T110	T450	T590/H	T650/H	T770/H	T870/H	S70	S100	S450	S510	S530/H	S550/H	S570/H	S590/H	S630/H	S650/H	S770/H	S850/H	A770/H		
Angle Broom, 122 cm	6907000	X							X														
① Angle Broom, 173 cm, ACD	6905805		X	X	X	X	X			X	X	X	X	X	X	X	X	X	X			X	
Angle Broom, 213 cm, ACD	6905806				X	X	X	X				X	X	X	X	X	X	X	X	X	X	X	X
Note: 7-Pin Attachment Control Kit is installed as standard on High Flow (H) machines.																							
② 7-Pin Attachment Control Kit **	6733142		X							X													
7-Pin Attachment Control Kit **	7229102			X							X												
7-Pin Attachment Control Kit **	7128426				X	X	X	X				X	X	X	X	X	X	X	X	X	X	X	X

WHEN NOT USED,
PUT IT ON THE STANDS
TO PREVENT BRISTLES
DAMAGE.