

Applications

Landscaping

Main features

Working widths of 96, 157 or 192 cm.

Bi-directional rotation allows both top-cutting and undercutting in either travel direction.

Offset mounting permits tilling next to sidewalks, curbs and buildings.

Hydraulically-powered; no shear pins to maintain.

Able to use high-flow hydraulics for enhanced performance on 62" and 76" models.

Hardened, double-edge, replaceable tines.

Exclusive Bob-Tach™ mounting system permits quick hookup to loader.


Forward/reverse travel direction.

Compatibility

Description	Item number	Compatible with loader Compatible with telescopic
Tiller 38in	6906144	S100, S70-E, T110-E, MT55, T2250
Tiller 40 in	7196028	S100, S70-E, T110-E, MT55, T2250
Tiller 62in	7104371	S130-E, S150-E, S160-E, T190-E, T320-B, S630-E, S185-E, S175-E, T190-B, S250-B, S650-E, T650-E, S205-E, S510-E, S530-E, S550-E, S550-B, S570-E, S590-E, T590-E, T2250
Tiller 76in	7102125	S160-E, T190-E, T320-B, S630-E, S185-E, S175-E, T190-B, S250-B, S650-E, T650-E, S205-E, S770-E, T770-E, A770-E, S530-E, S550-E, S550-B, S570-E, S590-E, T590-E, T2250

Characteristics and Performance

Description	Item number	Working width (mm)	Max. working depth (mm)	Number of tines	Required hydraulic flow (L/min)	Drive type
Tiller 40 in	7196028	966.0	102.0	32	34.0-68.0	Chain
Tiller 62in	7104371	1575.0	152.0	36	64.0-140.0	Direct drive
Tiller 76in	7102125	1918.0	152.0	44	64.0-140.0	Direct drive

Weights and dimensions


Description	Item number	Operating weight (kg)	Shipping weight (kg)	Overall Length (mm)	Overall Width (mm)	Overall Height (mm)
Tiller 40 in	7196028	261.0	277.0	709.0	1220.0	793.0
Tiller 62in	7104371	307.0	321.0	836.0	1797.0	614.0
Tiller 76in	7102125	347.0	361.0	836.0	2144.0	614.0