



# DROP HAMMER



	REQUIREMENTS	FEATURES & BENEFITS
	 <p>Drop Hammer: No special requirement.</p>	<ul style="list-style-type: none"> <li>• The Bobcat drop hammer efficiently demolishes concrete and asphalt up to 45 cm thick.</li> <li>• Because it generates little vibration or noise compared to standard hydraulic breakers, its the ideal demolition attachment for parking lots, driveways and sidewalks.</li> <li>• The standard Bob-Tach™ mounting system makes easy work of attaching and detaching the drop hammer and loader.</li> <li>• When not in use, the hammer stands upright. A cushioned safety valve permits the weight to fall slowly if hydraulic flow to the attachment is shut off or lost during mid-stroke.</li> <li>• The fast cycle time, 20 blows per minute, allows the operator three seconds to reposition and reset the loader between cycles.</li> </ul>

**Description:** The drop hammer is intended for demolition of large surface areas such as concrete roads and driveways. This high productivity breaker is reliable, easy to transport and delivers an unmatched breaking force.

TECHNICAL SPECIFICATIONS											
Description	Part Number	Flow (L/min)	Impact Energy (J)	Hammer Stroke (mm)	Overall Height (fully raised) (mm)	Cycle Time (strokes/minute)	Max. Concrete Thickness (mm)	Weight (Kg)	Control Kit Required	Working Flow	First use installation time
Drop Hammer	7137810	57	4882	965	1880	20	350 - 450	875	No	Standard	None

COMPATIBILITY CHARTS																						
Description	Part Number	Compact Track Loaders						Skid Steer Loaders and All-Wheel Steer Loaders														
		MT55	T110	T450	T590/H	T650/H	T770/H	T870/H	S70	S100	S450	S510	S530/H	S550/H	S570/H	S590/H	S630/H	S650/H	S770/H	S850/H	A770/H	
Drop Hammer	7137810				X	X	X	X				X	X	X	X	X	X	X	X	X	X	X