



	REQUIREMENTS	FEATURES & BENEFITS
	 <p data-bbox="655 658 927 683">Crane Jib: No special requirement.</p>	<ul data-bbox="1091 349 1458 434" style="list-style-type: none"> <li>• 4.1t capacity.</li> <li>• Strong design.</li> <li>• Easy to install thanks to the Quick-Tach system.</li> <li>• Short center of gravity (only 240 mm).</li> </ul>

**Description:** Add a crane jib and your telescopic handler is turned into a crane, but with all the advantages of its mobility and versatility.



Quick-Tach System (QT)  
(available on all models)



Manitou Carriage System (MT)  
(available on TL models only)

## TECHNICAL SPECIFICATIONS

Description	Part Number	Coupling System		Width (mm)	Capacity (kg)	Weight (kg)	Control Kit Required	Working Flow	First use installation time
		QT	MT						
Crane Jib 4.1t 0.7m, QT	7235647	X		830	4100	177	No	Standard	None
Crane Jib 4.1t 0.7m, MT	7204108		X	830	4100	177	No	Standard	None

## COMPATIBILITY CHARTS

Description	Part Number	Telescopic Handlers									
		TL358/+ TL26.60 TL30.60 TL30.70	TL360 TL34.65HF	TL470/HF TL35.70/ TL38.70HF	T35105/L T35.105/L	T36120SL T36.120SL	T35130S/SL T35.130S/ SLP	T35140S T35.140S	T40140 T41.140SLP	T40180 T40.180SLP	
Crane Jib 4.1t 0.7m, QT	7235647	X	X	X	X	X	X	X	X	X	
Crane Jib 4.1t 0.7m, MT	7204108	X	X	X							